



M50A Flex

High-efficiency three-phase solar inverters for large commercial rooftop and ground-mounted PV systems.



Wide input voltage range
(200 to 1000 V)

- Lightweight with IP66 housing for harsh environmental conditions
- No string fuses required
- Wall or ground mounting (optional)



Peak efficiency

- 6 MPP trackers for more flexibility when designing the PV system
- Anti-PID and arc detection
- Optional AC and DC surge protection devices type 1+2

55 kVA solar inverters

Input (DC)	M50A Flex	Communication	M50A Flex
Max. input voltage	1000 V _{DC} ¹⁾	Communication interfaces	2 x RS485, 2 x dry contacts, 1 x external power-off, 6 x digital inputs, Wi-Fi (optional), Sub-1G (optional)
Operating voltage range	200 to 1000 V _{DC}	Data visualization	DeltaSolar app, MyDeltaSolar Cloud
MPP voltage range	200 to 1000 V _{DC}	Display of operating status	3 LEDs
MPP voltage range with max. power	390 to 900 V _{DC}		
Nominal voltage	600 V _{DC}		
Max. current (per MPP tracker/total)	26 A/132 A		
Max. short-circuit current I _{SC}	50 A per MPP tracker		
Max. number of MPP trackers	6		
Max. number of module strings per MPP tracker	2		
DC surge protection devices	Type 2 (EN 61463-11), replaceable, combined Type 1+2 retrofittable		
Output (AC)	M50A Flex	Safety/Standards	M50A Flex
Max. apparent power ²⁾	55 kVA	Protection class	IP66
Max. active power ²⁾	55 kW ³⁾	Safety class	I
Nominal apparent power ²⁾	50 kVA	Configurable trip parameters	Yes
Voltage range ⁴⁾	230/400 V -20%/+30%, 3 phases + PE (Δ), 3 phases + N + PE (Y)	Insulation monitoring	Yes
Max. current	80 A	Overload behavior	Current limitation, power limitation
Frequency range ⁴⁾	50/60 Hz ± 5 Hz	Anti-islanding protection/grid regulation	VFR 2019 (Enedis-PRO-RES_10E, Enedis-PRO-RES_64E), VDE-AR-N 4105, EN 50549-1
Adjustment range of power factor	0.8 cap to 0.8 ind		
Total harmonic distortion (THD)	< 3% at nominal apparent power	EMC	EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12
Consumption in night mode ⁵⁾	< 3 W	Safety	IEC 62109-1/-2; CE compliance
AC surge protection devices	Type 2 (EN 61463-11), replaceable		
General Specifications	M50A Flex		
Delta model name	M50A_260		
Peak efficiency	98.7%		
Efficiency EU	98.3%		
Operating temperature range	-25 to +60°C		
Temperature range without power derating	-25 to +50 °C		
Storage temperature range	-25 to +60°C		
Relative humidity	0 to 100%, non-condensing		
Max. operating altitude	4000 m (above sea level)		
Topology	Without transformer		
Standard warranty	5 years (warranty extension available upon request)		
Mechanical design	M50A Flex		
Dimensions (H x W x D)	699 x 629 x 264 mm		
Weight	64 kg		
Cooling	Replaceable fan module		
Mounting options	Wall mounting ⁶⁾ , floor mounting ⁷⁾		
Disconnectors	2 mechanical DC disconnectors		
Connection type AC side	Screw terminals		
Connection type DC side	12 pairs of DC plugs Amphenol H4 ⁸⁾		

- 1) The max. voltage withstand is 1100 VDC. The inverter starts to work when the input voltage drops below 1000 VDC.
- 2) Cos Phi = 1 (VA = W)
- 3) At ambient temperatures ≤ 50°C.
- 4) AC voltage and frequency range are programmed based on the respective country regulations.
- 5) Night-time consumption with standby communication
- 6) Mounting plate included in scope of delivery
- 7) Mounting feet can be ordered separately
- 8) Included in scope of delivery

Email: solarsales.emea@deltaww.com

Telephone: **+49 7641 455 547** (phone number in Germany)